

# FUNMAT HT

## Desktop High-performance 3D Printer



### Multi-material printing capability

Can print high-performance materials such as PEEK, PEEK-CF, PEEK-GF, PEKK and other materials such as PA-CF, PA, PC, ABS.



### Maximized build volume ratio

Build volume can be up to 260 x 260 x 260 mm.



### Advanced Thermal Design

90 °C (194 °F) heated chamber,  
160 °C (320 °F) build plate and 450 °C (842 °F) nozzle.



### Intelligent Design

Auto-leveling, filament runout warning,  
remote video monitoring.

The advanced design of the FUNMAT HT makes it easy to adapt to lab and workshop environments. It offers a print size up to 260 x 260 x 260 mm with excellent part performance. With the FUNMAT HT you can print common engineering filaments as well as high-performance filaments such as PEEK, PEEK-CF, PEEK-GF, PEKK, and third-party materials.



## Technical Parameters

### Printing

<b>Technology</b>	FFF (Fused Filament Fabrication)	<b>Leveling</b>	Auto Leveling, Manual Leveling
<b>Build Volume</b>	260 x 260 x 260 mm (10.2 x 10.2 x 10.2 in)	<b>Materials*</b>	PEEK, PEEK-CF, PEEK-GF, PEKK, PPS, PC, PC-ABS, PA6/66, PA6-CF, PA12, PA12-CF, ABS, ASA, HIPS, PVA, Carbon Fiber-Filled, Glass Fiber-Filled, ESD-safe, etc.
<b>Layer Thickness</b>	0.1-0.5 mm		
<b>Number of Nozzles</b>	1		
<b>Number of Spools</b>	1 (Max 1 Kg/pc)		
<b>Filament Diameter</b>	1.75 mm	<b>Nozzle Temperature</b>	Max. 450 °C (842 °F)
<b>Print Speed</b>	Max. 120 mm/s	<b>Build Plate Temperature</b>	Max. 160 °C (320 °F)
<b>Nozzle Diameter</b>	Default: 0.4 mm (Optional: 0.25/0.6/0.8 mm)	<b>Chamber Temperature</b>	Max. 90 °C (194 °F)
		<b>Functions</b>	Filament Runout Warning

### Machine

<b>Voltage</b>	100 ~ 132 V/15 A or 200 ~ 240 V/7 A. 50/60 Hz	<b>Build Chamber</b>	Fully Enclosed Printing Chamber
<b>Max. Power</b>	1200 W	<b>Motor System</b>	High Performance Standalone Driver
<b>Connectivity</b>	USB, SD Card	<b>Cooling</b>	Fan
<b>Screen</b>	3.2" Touch Screen	<b>Travel Speed</b>	Max. XY 200 mm/s
<b>Build Plate</b>	Ceramic Glass Plate, with Magnetic Fixations	<b>Resolution</b>	XY: 15.6 µm; Z: 1.56 µm
		<b>Printer Size</b>	543 x 501 x 645 mm (21.3 x 19.7 x 25.4 in)
		<b>Printer Weight</b>	63 Kg (139 lb)

### Safety

<b>Safety Design</b>	Overload Protection, Closed Chamber, Warning Labels
<b>Safety Standards</b>	EN60204
<b>Certification</b>	CE, FCC, SGS

### Slicing

<b>Slicing Software</b>	INTAMSUITE™
<b>Supported File Types</b>	.stl/.obj/.x3d/.3mf/.stp/.iges
<b>Operating System</b>	Windows

### Operating Environment

<b>Working Temperature</b>	15 °C ~ 32 °C (59 ~ 89.6 °F)
<b>Working Humidity</b>	30 ~ 70 %
<b>Storage Temperature</b>	0 °C ~ 54 °C (32 ~ 129.2 °F)
<b>Storage Humidity</b>	10 ~ 85 %

\*Printing materials are not limited to this table, recommended printing materials are fully validated on the printer.